

## PRODUCT APPLICATIONS CHART ITL Coated Woven PE

APPLICATIONS		12	16	20	24	30 LT	30*	40	40 GL
	Well Pad	Х	Х	NR	A2	A2	A2	А3	А3
	Frac Tanks	Х	Х	NR	A2	A2	A2	А3	А3
<b>Containment Liners</b>	Freshwater	NR	NR	Α	Α	Α	Α	Α	Α
	Equipment	Х	Х	NR	Α	A2	A2	А3	А3
	Coal Slurry	Х	Х	NR	Α	A1	Α	Α	Α
	Recreational Ponds	NR	NR	Α	Α	Α	Α	Α	Α
	Temporary	NR	NR	Α	Α	Α	Α	Α	Α
Water Storage	Stormwater	NR	NR	Α	Α	Α	Α	Α	Α
	Agricultural Ponds	NR	NR	Α	Α	Α	Α	Α	Α
	Drinking water	NR	NR	A4	A4	A4	A4	A4	A4
	Treated Flowback Fluid	Х	Х	Х	NR	NR	А3	А3	А3
	Production Fluid	Х	Х	Х	NR	NR	А3	А3	А3
Fluid Storage Other	Oil **	Х	Х	Х	NR	NR	А3	А3	А3
	Acids **	Х	Х	Х	NR	NR	А3	А3	А3
	Gasoline Unleaded **	Х	Х	Х	NR	NR	А3	А3	А3
	Soil - Contaminated	Α	Α	Α	Α	Α	Α	Α	Α
	Soil - Clean	A	A	A	A	A	A	A	A
	Wheat , Hay , corn	A	A	A	A	A	A	A	A
Stockpile Covers	Landfill Daily Cover	A	Α	A	A	A	A	A	A
	Salt	A	Α	A	A	A	A	A	A
	Wood Chips	Α	A	Α	A	Α	Α	A	A
	Sand	Α	A	Α	Α	Α	Α	Α	A

## **KEY**

A Acceptable

X Not Acceptable

NR Not Recommended

- 1 May be acceptable with geo underlayment required
- 2 May be acceptable with geo underlayment and overlayment
- 3 Subgrade
  Subgrade is anticipated to meet ITL
  acceptance specification (attached)
  site conditions may determine whether
  geotextiles are required.
- 4 ITL woven coated products are not NSF potable approved

## ITL 30\*

EPA 9090 Tested and approved for frac flowback by PA DEP.

## **State Regulations**

When applicable, check your individual State regulations for specifications and minimum requirements.

The above chart is to be used as a guideline only based on past usage of ITL products. ITL neither represents nor warrants a products suitability for any specific project.

<sup>\*\*</sup> Please contact an ITL Sales Representative regarding these Fluid Storage Applications.